





- Intel® Core™ i7-7820EQ Processor
- 15.6" TFT LCD FHD with Getac QuadraClear® sunlight readable display
- Optional NVIDIA® Quadro® P2000 4GB discrete graphics controller
- Multimedia bay & PCI/PCIe 3.0 expansion unit











### **SPECIFICATIONS**

Operating System	Windows 10 Pro
Mobile Computing Platform	Intel® Core™ i5-7440EQ 2.9GHz Max. 3.6GHz - 6MB Intel® Smart Cache  Platform options: Intel® Core™ i7-7820EQ 3.0GHz Max. 3.7GHz - 8MB Intel® Smart Cache
VGA Controller	Intel® HD Graphics 630 Optional: NVIDIA® GeForce® GTX1050 4GB discrete graphics controller Optional: NVIDIA® Quadro® P2000 4GB discrete graphics controller
Display	15.6" TFT LCD FHD (1920 x 1080) Protection film 1,000 nits QuadraClear® sunlight readable display Optional: Resistive touch screen
Storage & Memory	8GB DDR4 Optional: 16GB / 32GB / 64GB DDR4 <sup>1</sup> 500GB SATA HDD / 512GB SATA SSD Optional: 1TB SATA HDD / 1TB / SSD
Keyboard	LED backlit membrane keyboard with integrated numeric keypad Optional: LED backlit rubber keyboard
Pointing Device	Touchscreen - Optional: Pressure sensitive touchscreen Touchpad - Glide touchpad with scroll bar
Expansion Slots	Smart card reader x 1 ExpressCard/54 x 1 Optional: PCMCIA Type II x 1



Multimedia Bay DVD super multi drive

Optional  $2^{nd}$  storage: 500GB HDD / 1TB HDD / 512GB SSD / 1TB

SSD

Optional 2<sup>nd</sup> battery: 10.8V, 9240mAh, 99.8Wh

I/O Interface Audio input (Mini-jack) x 1

Audio output (Mini-jack) x 1

DC in Jack x 1

USB 3.2 Gen 1 Type-A x 4

LAN (RJ45) x 2 HDMI x 1

Docking connector x 1

External VGA (15-pin; D-sub) x 1 Serial port (9-pin; D-sub) x 2 Optional: FHD webcam x 1

Optional: RF antenna pass-through for GPS  $^{\mathrm{ii}}$ , and WLAN

Communication Interface 10/100/1000 base-T Ethernet

Intel® Dual Band Wireless-AC 8265, 802.11ac

Bluetooth (v4.2) iii
Optional: Dedicated GPS

Pre-installed Software Getac Utility

**Getac Geolocation** 

Optional: Absolute Persistence®

Security Features TPM 2.0

Kensington lock Intel® vPro™ Technology Smart card reader

Power AC adapter (150W, 100-240VAC, 50/60Hz)

Li-ion smart battery (10.8V, 9240mAh, 99.8Wh)

Optional: Multimedia bay 2<sup>nd</sup> Li-ion smart battery (10.8V,

9240mAh, 99.8Wh)

**Dimension (W x D x H) & Weight** 410 x 320 x 65mm (16.1" x 12.6" x 2.5")

5.2 kg (11.4 lbs) iv

Rugged Features MIL-STD-810H certified

IP65 certified

MIL-STD-461G certified <sup>v</sup> Vibration & drop resistant Full magnesium alloy case

Shock-protected removable HDD

Optional: ANSI/UL 121201, CSA C22.2 NO. 213 (Class I, Division

2, Groups A, B, C, D) vi

#### **Environmental Specifications**

Temperature vii:

- Operating: -20°C to 55°C / -4°F to 131°F

- Storage: -40°C to 71°C / -40°F to 160°F

Humidity:

- 95% RH, non-condensing

#### **Accessories**

Battery (10.8V, 9240mAh, 99.8Wh) AC adapter (150W, 100-240VAC)

#### Optional:

Backpack

Battery (10.8V, 9240mAh, 99.8Wh)

Multimedia bay 2<sup>nd</sup> HDD

Multimedia bay 2<sup>nd</sup> battery (10.8V, 9240mAh, 99.8Wh)

Multi-Bay charger (Dual-Bay) AC adapter (150W, 100-240VAC)

Office dock AC adapter (150W, 100-240VAC)

MIL-STD-461 certified AC adapter (150W, 100-240VAC)

Stylus

Protection film

PCI or PCI-Express 3.0 expansion unit (x2 slots) viii

Vehicle dock viii
Office dock viii

#### **Bumper-to-Bumper Warranty**

Accidents can take your equipment out of service when you least expect it, especially in a rugged environment, which can cause costly equipment downtime.

That is why Getac has introduced accidental damage as standard under our Bumper-to-Bumper warranty, to help minimize your enterprise IT costs.

Bumper-to-Bumper is your hassle-free guarantee. That means you can depend on us to have your unit back in service within days.

#### Standard

5 years Bumper-to-Bumper

- I. Share memory size may vary by different operating system and RAM size.
- II. Optional RF antenna pass-through for GPS, PCI or PCI-Express expansion unit are mutually exclusive options.
- III. Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area.
- IV. Weight and dimensions vary from configurations and optional accessories. Depth including hard handle.
- V. MIL-STD-461G 150W AC adapter sold separately.
- VI. PCI or PCI-Express 3.0 expansion unit is not available with ANSI/UL 121201, CSA C22.2 NO. 213 configurations.
- VII. Tested by an independent third-party test lab following MIL-STD-810H.
- VIII. PCI or PCI-Express 3.0 expansion unit is not compatible with vehicle dock and office dock.

Information provided herewith is for reference only, available specification shall be subjected to quotation by request.



	Vehicle Dock	Office Dock
Serial Port	2	1
External VGA	1	1
Microphone	1	1
Audio Output	1	1
DC in Jack	1	1
USB	USB 2.0 x 4	USB 3.0 x 2 USB 2.0 x 2
LAN	1	1
RF Antenna Connector	3 (optional)	-

#### **GETAC TECHNOLOGY CORPORATION**

5F, Building A, No. 209, Section 1, Nangang Rd.,
Nangang Dist., Taipei City, 11568, Taiwan, R.O.C.
Tel: +886 2 2785 7888
globalmarketing@getac.com I www.getac.com
Copyright © 2021 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved.

Information provided herewith is for reference only, available specification shall be subjected to quotation by request.